



Magna™ RD Range

Rock Drill Oils

Description

Castrol Magna RD Range Oils (previously called Rock Drill™ Oils) consist of selected mineral oils specially compounded with lubricity fortifiers, corrosion inhibitors and tackiness additives.

Application

Mining, quarrying, constructions, roadworks, tunneling and excavations.

Magna RD oils are recommended for the following well-known companies including Gardner-Denver, Atlas Copco and SIG.

However the correct grade should be selected against specific equipment and for local operating conditions. Most manufacturers include selection charts in their handbooks to assist in the selection of the correct grade.

Advantages

Design features and benefits of the Castrol range of high quality rock drill oils include:

- High film strength.
- Reduced friction.
- Provide a suitable seal between piston and cylinder.
- Reduced wear.
- Helps maintain maximum percussion efficiency.
- Preferentially adhere to metal surfaces and resist blow-off.
- Improved protection wear against wear caused by poor lubrication.
- Helps maintain operating speed.
- Reduced wear, allows operation in conditions of high or low temperatures.

Typical Characteristics

Name	Method	Units	RD 100	RD 150	RD 320
ISO Viscosity Grade	-	-	100	150	320
Density @ 15°C	ASTM D4052 / ISO 12185	g/cm ³	0.89	0.89	0.90
Kinematic Viscosity @ 40°C	ASTM D445 / ISO 3104	mm ² /s	100	150	320
Kinematic Viscosity @ 100°C	ASTM D445 / ISO 3104	mm ² /s	11.2	14.7	24.2
Pour Point	ASTM D97 / ISO 3016	°C	-15	-12	-12
Flash Point - open cup method	ASTM D92 / ISO 2592	°C	>215	>220	>250

Subject to usual manufacturing tolerances

This product was previously called Rock Drill. The name was changed in 2015.

Magna™ RD Range

02 Jun 2016

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 717 Bourke Street, Docklands Vic 3008

Technical Advice Line: 1300 557 998 Customer Service: 1300 722 088

<http://msdspd.castrol.com>